



cable equipment, inc.

HEADENDS

FIBER OPTICS

DIGITAL | IPTV

INSTALLATIONS

SYSTEM BALANCING

ANTENNA INSTALLS

ONSITE SUPPORT

ENGINEERING

DESIGN

DOCSIS 3.1

DPX-42/1220

5-42, 54-1220 GHz
Diplex Filter



DPX-85/1220

5-85, 102-1220 GHz
Diplex Filter



DPX-204/1794

5-204, 258-1794 GHz
Diplex Filter



TIBA-30-1220 | TIBA-40-1220

2 Way 1220 MHz Amplifier,
30 or 40 dB Gain



TIN40RD31-85

Indoor Optical Node



TDA31-34/1200

DOCSIS 3.1 Amplifier 5-1220 MHz,
34 dB Gain 105-1220 MHz
Forward, 18 dB 5-85 MHz Reverse

ATSC 3.0



Televés

H30D+FULL

8VSB | ATSC 3.0
DOCSIS 3.1
Signal Level Meter

WELLAV

TXS3800

ATSC 3.0 to TS
Multi-Channel Transcoder



ARD3100 / ARD3400

Receiver Decoder 1 / 4 Program

RF Broadband



TPA-20U & VHF

UHF & VHF Preamp

DDA Series Amplifiers

Digital Drop Amplifiers
Active & Passive Reverse Models
1 or 4 Outputs, 8 or 15 dB Gain



LTE-608

Cellular
Interference Filter



T2 Series

Coax Hardline
Connectors & Adapters

L-Band / Fiber Optics

OTDR-1315

Optical Time Domain
Reflectometer



QLink 04T

Quad Fiber Transmitter
L-Band Satellite Link &
Outdoor Enclosure



MAG

20541 & 20523

C-Band Interference Filter
Red 3820-4200 MHz
Blue 4000-4200 MHz



TLT-X-SM-XXX-X-G652

Loose Tube Fiber Optic Cable

Norsat International Inc.



3120C

PLL C-Band LNB 3120C,
20°K, ±5KHz L.O. Stability



Headend Electronics



OMNIHUB-X100

Entry Level transcoder 3 HD / 12 SD services H.264/MPEG-2 linear transcoding, or 1 HD / 6 SD H.264/MPEG-2 ABR transcoding with 4 profiles

OMNIHUB-X200

High Performance transcoder 10 HD / 40 SD services H.264/MPEG-2 linear transcoding, or 5 HD / 20 SD services H.264/MPEG-2 ABR transcoding with 4 profiles



OMNIHUB-16

16 Module Chassis
Dual Power Supplies



OMNIHUB-PLAY200

IPTV System - Standard package local VOD Unicast(HLS) mode: support up to 60 live SD/HD channels and 500 devices. Multicast mode: support up to 150 channels and 500 devices

OMNIHUB-PLAY100

IPTV System - Basic package Unicast(HLS) mode: support up to 30 live SD/HD channels and 200 devices. Multicast mode: support up to 30 channels and 200 devices



IMPULSE 300D

Network IP Decoder



IMPULSE 200E

Network Encoder/Streamer



OMNIHUB-6

6 Module Chassis
Single Power Supply



NEA-40-D31

1.2 GHz Rackmount 2 Way Headend Amplifier, GaAs Hybrid, 40 dB Gain



LPTVBA-02

2 Program MPEG 2/4 Encoder SDI In, EAS, Dual P/S, ATSC Tables for LPTV



UMH160R

SD/HD IRD Integrated Receiver Decoder



DIP3200A

Digital IP to Analog Modulator, 32 Channel



T9261-E / T9261-D

Ultra-HD HEVC, 1080P AVC, 1080i MPEG2 Encoder / Decoder



FlexLink S2B

L8:24 L-Band Matrix Switch

Toner's NEW line of minimods are a direct replacement for the recently discontinued Blonder Tongue minimod series.



- TMM45-*** Mini Saw Filtered Modulator
- TAMM-860** Mini Agile Modulator
- TAMM-QAM** Mini Agile HD QAM Encoder Modulator
- TAMMC-QAM** Agile SD QAM Encoder Modulator
- TMMPS** Minimod Power Supply
- TMMRC-12** Minimod Rack Chassis



DEVISER

C1200+
QAM/Analog Signal Level Meter



DOCSIS 3.1 | FIBER OPTIC DISTRIBUTION | IPTV | SETTOPS | MODEMS
ENCODERS | DECODERS | HEVC | 4K | UHD | ABR | OTT | TRANSCODING
DIGITAL SOLUTIONS | IRD's | QAM | TEST EQUIPMENT



DEVISER



969 Horsham Road, Horsham, PA 19044
800-523-5947 | 215-675-2053
info@tonercable.com
www.tonercable.com